

Castrol Radicool SF-O Premix

Castrol Radicool SF-O Premix is a premium, nitrite-free, ethylene glycol-based antifreeze/coolant that utilizes advanced Organic Acid Technology (OAT) and specialized additive technology for superior, extended-life protection. Designed for heavy-duty applications, Radicool SF-O Premix eliminates the need for SCAs, reducing maintenance and ensuring reliable performance. It meets the stringent nitrite-free requirements of leading OEMs.

Real-world challenges

The cooling system controls temperatures of all metallic and non-metallic material, along with other engine fluids. To properly transfer heat, you must protect system components from corrosion, cavitation, and scale. More than 40% of engine problems originate in the cooling system. Coolant selection and maintenance is key to the life of equipment.



Superior protection and reduced cooling-system maintenance.

ates

Castrol® Radicool™ advantages

- Free of phosphates, silicate, nitrites, amines, and borates
- Offers excellent cavitation protection for wet sleeve liners
- Contains better heat-transfer properties than conventional coolants requiring SCAs. Eliminates maintenance with no SCAs required
- Provides freeze and boil-over protection
- Extended life corrosion protection for steel, solder, copper, iron, brass, and aluminum
- · High-quality defoamer system; non-harmful to hoses, plastics, or gaskets
- Compatible with most major American brands of coolant technologies including conventional and Organic Acid Technology (OAT)

Extended service life up to 1,000,000 miles or 20,000 hours*

* Proper inhibitor level should be determined by coolant testing. The recommended test interval is 300,000 miles, 6,000 hours or 1 year, whichever comes first.

Product performance

MB BB00.40-P-0310-01A, **ASTM D3306** Cummins CES 14603 IVECO Standard 18-1830 325.3/326.3 **ASTM D6210** JCB STD00088 Cummins CES 14636 MTU 5048 **ASTM D7583** Daimler DBL 7700.00 GE Jenbacher 1000-201 MWM Deutz TR0199-99-1115 **Behr Radiator** Detroit Diesel 93K217 John Deere JDM H24C MWM Deutz TR0199-99-2091 BS 6580:2010 Deutz H 0685-7: Class John Deere JDS-G135 Navistar CEMS B-1 Type IIIA DQC CB-14 CAT EC-1 Komatsu KES 07 892 Navistar MPAPS B-1 Type IIIA Ford ESE-M97B44-A **CNH MAT 3620** Liebherr Paccar CS0185 Grade EG3/EG4 Ford WSS-M97B44-D Mack GS17004 TMC RP 338A **CNH MAT 3624** Ford WSS-M97B51-A1 MAN 324 Type SNF Volvo Coolant VCS:20774185 Cummins CES 14439 GET-2594F (MI-09500) **MAXXFORCE** Waukesha 4-2429H

To learn more about Castrol Radicool SF-O Premix and how it can help maximize your fleet's performance and lower overall operating costs, please contact your Castrol sales representative.

