

Castrol Transmax ATF/CVT Universal is a technologically advanced full synthetic formulation designed to deliver excellent performance in most of the traditional stepped automatic transmissions and Continuously Variable Transmissions currently in use. It is blended with premium base oils and an additive package that utilizes Castrol Smooth Drive® Technology. This is the first Castrol multi-vehicle ATF suitable for use in both step-shifting and continuously variable automatic transmissions. It is also suitable for use in a range of Hybrid applications. Castrol Transmax® ATF/CVT Universal is suitable for use in vehicles manufactured in North & South America, Europe, and Asia.

Features and Benefits

- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Unsurpassed protection against copper corrosion
- Broad scope of vehicle applications improves workshop efficiency and inventory management

Suitable for use* in the following Step Shifting Transmission Applications:

- GM – All vehicles Calling for DEXRON®-VI or previous
- Ford – All vehicles from 1983 to current model year, excluding Mercon® ULV applications
- Chrysler – All vehicles calling for ATF+4® or previous
- Audi - All six-speed automatic transmissions
- BMW - All six-speed automatic transmissions
- Honda/Acura ATF-Z1, ATF DW-1
- Hyundai - All applications that require automatic transmission fluid
- Isuzu – All vehicles that require DEXRON® III
- Jaguar - All six-speed automatic transmissions
- Kia - All applications that require automatic transmission fluid
- Mazda ATF M-III, MV, T-IV, JWS 3317, FZ
- Mercedes 236.1, 236.2, 236.5, 236.6, 236.7, 236.8, 236.9, 236.11, 236.12, 236.14, 236.15, 236.16, 236.17, 236.41
- Mini Cooper - All six-speed automatic transmissions
- Mitsubishi - All applications that require automatic transmission fluid
- Nissan/Infiniti - All applications that require automatic transmission fluid
- Peugeot - All six-speed automatic transmissions
- Porsche - All six-speed automatic transmissions
- Saab - All six-speed automatic transmissions
- Saturn – All vehicles that require T IV (JWS 3309)
- Subaru - All applications that require automatic transmission fluid
- Suzuki - All applications that require automatic transmission fluid
- Toyota/Lexus - All applications that require automatic transmission fluid

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

- Volkswagen - All six-speed automatic transmissions
- Volvo - All six-speed automatic transmissions
- ZF 3 through 9 speed automatic transmissions
- Various Domestic/European vehicles where DEXRON® IIIH or prior is required

Suitable For Use in the following CVT applications:

Audi Multitronic
BMW Mini Cooper
Chery CVT
Daihatsu AMMIX
Daihatsu Fluid TC
Ford CVT
Fujjyuko i-CVT
GM/Saturn DEX-CVT
Honda CVT**
Hyundai/Kia CVT
Idemitsu CVT
Lexus Fluid TC, Fluid FE
Mazda JWS 3320
MG Rover EM-CVT
Mini Cooper CVT
Mitsubishi CVTF
Mitsubishi Diaqueen) CVT
Mitsubishi CVTF ECO J4
Nissan NS-1, -2, -3
Punch CVT
Renault Elf Matic CVT
Shell Green IV
Subaru iCVT
Subaru Lineartronic CVT
Suzuki CVT
Toyota CVT
Volvo CVT
VW/Audi CVT

**Transmax ATF/CVT Universal is suitable for use in all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch

Suitable For Use in the following Hybrid applications:

Ford Escape Hybrid with eCVT
Honda e:HEV
Honda iMMD
Jatco JR712E
Jatco CVT 8 Hybrid Mazda SKYACTIVE-HYBRID
Nissan ePower

**"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Nissan Altima Hybrid
Tesla Model S and Model 3
Toyota THSII/Toyota Prius
Toyota THS 5th Gen. / Toyota Noah, Voxy etc.

Detailed Step Shifting Automatic Transmission Applications:

Acura ATF Z-1
Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1
Aisin Warner T IV
AS 68 RC (T IV)
ATF RED 1, RED 1K
Audi 5 HP LT 71141 (ZF 5 HP 18FL/19FL/24A)
Audi 5 HP LT 71141 (Audi G-052-162-A1/A2)
Audi 5 HP (ZF 5 HP 30)
Audi G-055-025-A2 (JWS 3309)
Audi G 052 025 A2
Audi G 052 055
Audi G 053 025 A2
Audi G 052 162 A1/A2
Audi G 052 162 (ZF Lifeguardfluid 5), (ZF No.S671 090 170)
Audi G 055 162 A2, A6 (ZF Lifeguardfluid 6), (ZF No.S671 090 281)
Audi G 060 162 (ZF Lifeguardfluid 8), (ZF No.S671 090 312)
Audi G 052 190 A2
Audi G 052 990 A2
Audi G 055 540 (A2)
Audi G 055 005 A2
Audi G 055 025 A2 (JWS3309)
Bentley PY112995PA
BMW ETL-7045
BMW ETL-7045E
BMW LA2634
BMW 5 HP LT 71141(ZF 5 HP 18FL/19FL/24A)
BMW 5 HP (ZF 5 HP 18FL, 5HP24, 5HP30)
BMW ETL-8072B
BMW/Mini JWS 3309
BMW ATF 7
Bosch TE-ML 09
CAT TO-2
Chrysler 68049954AC
Daewoo LT 71141
Daihatsu AMMIX ATF D-II
Daihatsu AMMIX ATF D-III SP
Esso LT 71141
Ford – All vehicles from 1983 to current model year, excluding Mercon® ULV applications
Ford Mercon®
Ford Mercon® V
Ford FNR5 (Mazda M5, XT-9-QMMS)
Ford WSSM2C 138CJ, 166H

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Detailed Step Shifting Automatic Transmission Applications (continued):

Ford WSS M2C922A1, (24A (XT-8-QAW) JWS 3309
Ford/Lincoln/Mercury XT-2-QDX (M)
Ford/Lincoln/Mercury XT-2-QSM (Syn)
Ford ESP-M2C166H, XL-12
Fuso ATF-II
Fuso ATF-SPIII
Fuso ATF-A4
GM – All Vehicles that require DEXRON®-VI or Previous ATFs
GM 9986195 (Aisn AW, JWS 3309)
GM AW 1
GM DEXRON-II
GM DEXRON-IIIIH
GM TASA
GM T IV ATF
GM WS ATF
GM 1940700
GM 1940767
GM 21005966
GM 22717466
GM 88900925
GM 93160393
GM/GMC/Opel/Saturn AW1
GM/GMC/Opel/Saturn VI
GM/GMC/Opel/Saturn 88863400
GM/GMC/Opel/Saturn 88863401
Hino Blue Ribbon ATF
Honda/Acura Z-1
Honda/Acura Premium
Honda ATF Ultra II
Honda Type 3.0
Honda Type 3.1
Hyundai Diamond SP-II
Hyundai Diamond SP-III
Hyundai Diamond SP-IV
Hyundai Diamond SP-IV-M
Hyundai Diamond SPH-IV
Hyundai/Kia SP-IV (00232-1904/04500-00115)
Hyundai/Kia SP-IV M (SP4-M)
Hyundai/Kia SP-IV M1 (SP4-M1)
Hyundai/Kia SPH-IV
Hyundai/Kia SP-IV-RR
Hyundai/Kia SP-III
Hyundai/Kia Dex-II/SP-II

Hyundai/Kia JWS 3314
Hyundai/Kia NWS 9638

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Detailed Step Shifting Automatic Transmission Applications (continued):

Hyundai/Kia 040000C90SG
Hyundai/Kia NUMM040 CH20 Red-1
Idemitsu K17 3100 PL085
Infinity Matic-D
Infinity Matic-J
Infinity Matic-K
Infinity Matic-S
Isuzu Besco ATF II
Isuzu Besco ATF III
Isuzu Besco ATF SP
Isuzu SCS Fluid
Isuzu 08200-9001
Isuzu Genuine ATF
Jaguar ATF 3403 M115, ATF 3403-M115
Jaguar ATF 71141, ZF 5HP24
Jaguar JLM 20238
Jaguar ATF 3403 JLM20238
Jaguar K17
Jaguar JLM 20292
Jaguar Fluid8432
JASO 1A (M315-2004)
JASO M315-2013 1A
JASO M315-2013 1A-LV
JASO M315-2013 2A
Jaguar WSS-M2C922-A1
JEEP ATF+3
Kia SP-II
Kia SP-III
Kia SP-IV
Kia SP-IVM
Kia Red-1
Land Rover ATF M-1375.4
Land Rover LR023288
Lexus JWS 3309
Mazda ATF D-II
Mazda ATF MIII
Mazda ATF M-V
Mazda ATF FZ
Mazda ATF F-1
Mazda ATF S-1
Mazda ATF N-1

Mazda ATF 3317
MB 236.1
MB 236.2
MB 236.5

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Detailed Step Shifting Automatic Transmission Applications (continued):

MB 236.6
MB 236.7
MB 236.8
MB 236.9
MB 236.10
MB 236.11
MB 236.12
MB 236.14
MB 236.15
MB 236.16
MB 236.17
MB 236.41
MB ZF 4HP20
Mini Cooper T-IV
Mitsubishi Diamond Queen ATF-J2
Mitsubishi Diamond SP
Mitsubishi Diamond SP-II
Mitsubishi Diamond SP-III
Mitsubishi Diamond SP-IV
Mitsubishi Diamond SP-IV-M
Mitsubishi Diaqueen SK
Mitsubishi Diaqueen SP-II
Mitsubishi Diaqueen SP-III
Mitsubishi Diaqueen SP-IV
Mitsubishi Diaqueen AW
Mitsubishi Diaqueen J2
Mitsubishi Diaqueen J3
Mitsubishi Diaqueen ATF-MA-1
Mitsubishi Diaqueen ATF PA
NAG1 (Chrysler, Jeep, Cherokee)
Nissan ATF
Nissan Matic-D
Nissan Matic-J
Nissan Matic-K
Nissan Matic-S
Opel/GM 19 40 700
Opel/GM 19 40 707
Opel/GM 19 40 767
Opel/GM 21005966 Transaxle
Opel/GM 22017466

Opel/GM 88900925
Opel/GM 9986195
Peugeot ZF 4HP20
Peugeot/Citreon Z 000169756
Peugeot/Citreon (PSA) AL4 Automatic Gearbox oil (#9730.AE)

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Detailed Step Shifting Automatic Transmission Applications (continued):

Porsche ZF 5HP19FL
Porsche ZF 5HP20
Porsche ATF 3403-M115
Porsche LT 71141
Porsche T IV (JWS 3309)
Porsche 000 0430205 09
Porsche 999 917 547 00 (A2)
Porsche 000 043 205 28
Porsche Z 000169756
Renault DPO/AL4
Renault Matic D2
Renault Samsung SATF-D
Saab T IV (JWS 3309)
SAAB 93 165 147
Saab 93 160 393
Saturn T IV (JWS 3309)
Scion (All Vehicles)
Shell ATF 3405
Shell M115
Shell 12108
Shell LA 2634
Ssang yong DSIH 5N-66
Subaru ATF
Subaru ATF-HP
Subaru Dexron-II
Subaru K0140Y0700
Subaru ATF 5AT
Suzuki ATF AW-1
Suzuki AT Oil 5D06
Suzuki ATF 2306
Suzuki ATF 2384K
Suzuki ATF 3309
Suzuki ATF 3314
Suzuki ATF 3317
Texaco ETL-7045E
Texaco ETL-8072B
Texaco N402
Toyota ATF D-II

Toyota ATF D-III
Toyota Type T
Toyota Type T-II
Toyota Type T-III
Toyota Type T-IV (JWS 3309)
Toyota Type WS (Hybrid)

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.

Detailed Step Shifting Automatic Transmission Applications (continued):

Toyota Type WS (JWS 3324)
Volvo T IV (JWS 3309)
Volvo 97325
Volvo 97335
Volvo CE 97340
Volvo 97341
Volvo P/N 1161621
Volvo P/N 1161450/1161640
Volvo P/N 31256774/31256675
Volvo P/N 11614540-8
VW 5 HP LT 71141 (ZF 5 HP 18FL/19FL/24A)
VW 5 HP LT 71141 (VW G-052-162-A1/A2)
VW 5 HP (ZF 5 HP 30)
VW G-055-025-A2 (JWS 3309)
VW P/N G 052 025 A2
VW P/N G 052 055
VW P/N G 052 162 (ZF Lifeguardfluid 5)
VW P/N G 052 990 A2
VW P/N G 055 005
VW P/N G 055 005 A2
VW P/N G 055 162 A2, A6 (ZF Lifeguardfluid 6 Plus)
VW P/N G 055 540 A2
VW P/N G 052 25
VW P/N G 060 162 (ZF Lifeguardfluid 8)
VW P/N GUS 000 162
VW TL 521 62
VW TL 52540-A
Vickers M2950-S, I-286-S
Voith Svc Bltn #013 and #118
ZF all 3 & 4 Speed Transmissions
ZF 8-Speed Transmissions & ZF 9AT*

Detailed Continuously Variable Transmission Applications:

Audi Multitronic
BMW Mini Cooper EZL 799/ 83 22 0 136 376/ 83 22 0 429 154
Chery CVT
Chery WCF-1/Shell SL 2100

Daihatsu AMMIX CVTF DFE
Daihatsu AMMIX CVT Fluid DC
Daihatsu AMMIX CVT Fluid DFC
Daihatsu Fluid TC
Dodge/Jeep/Chrysler NS-2
Dodge/Chrysler/Jeep/Mopar CVT+4
Ford WSD-M2C-199A
Fujjyuuko i-CVTF FG
GM/Saturn DEX-CVT
GM/Saturn DEX-CVT, GM1940713 and 1940714
GM VT40/GM HP CVT
Honda Multimatic HMMF **
Honda HCF2**
Honda Z-1 (CVTmodel)*
Honda CVT**
Honda HMMF Ultra (for CVT without a starting clutch)
Hyundai/Kia CVT-1, SP CVT-1 and CVT-J1

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification

Detailed Continuously Variable Transmission Applications (continued):

Hyundai/Kia CVT-1
Hyundai/Kia SP III (CVT model)
Idemitsu CVTS-EX1
JWS 3401
Lexus Fluid TC, Fluid FE
Mazda JWS 3320
MG Rover EM-CVT
Mini Cooper EZL/EZL 799A.ZF CVT V1
Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)
Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)
Mitsubishi (Diaqueen) SP-III (CVT model only)
Mitsubishi CVTF ECO J4
Mitsubishi CVT Fluid-MA1
Nissan NS-1, -2, -3
Opel/Vauxhall 7-speed CVT, 95529854
Punch CVT (without starting clutch)
Punch CVTF EX-1 for VT2/VT3/VT5 Transmissions
Renault Elf Matic CVT
Shell Green 1V
Subaru iCVT, iCVT FG, ECVT
Subaru Lineartronic chain CVT and CVT II Fluid, K0425Y0710 & K0425Y0711
Subaru Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700
Subaru NS-2
Suzuki CVTF TC
Suzuki CVTF 3320 & Suzuki CVTF 4401
Suzuki NS-2

Suzuki CVT Green 1 & 2
Suzuki CVT Green IV
Toyota CVTF TC & FE
Volvo CVT 4959
VW/Audi TL 521 16 (G 052 516)
VW/Audi TL 521 80 (G 052 180)

**Transmax ATF/CVT Universal is suitable for use in all of Honda CVTs
except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch

*"Suitable for use" means that, based on testing (and technical judgments) by Castrol (and its suppliers), a fluid meets the performance requirements and other attributes of a particular specification, making it suitable for use in that specification. This is compared to an "OEM Approved" fluid which has gone through the OEM approval process and has been formally approved by the OEM for use in a particular specification.